

LCD 170



4:3

DISPLAY

CAPACITIVE
MULTI-TOUCH

INTEGRATED*
CUSTOMER
DISPLAY

DALLAS*
READERMSR*
READER

IP65

www.rmupos.co.uk

CONFIGURATION

LCD 150

LCD	17" LED
Luminosity	300 nits
Resolution	1280 x 1024
Touch Screen	PCAP Touch
View angle	0° ~ 90°

INPUT / OUTPUT

USB	1x USB 2.0 (Type A) 1x USB 2.0 (Type B to PC)
VGA	1x DB15
On/off button	2 (Power, Auto) + LED

POWER

Power supply	36W / 12V
DC Jack	1x 2 pin

OPTIONS

MSR	3-Track MSR (USB)
iButton	iButton (USB)
Customer display	LCM display 2 x 20 c. (USB)

CERTIFICATION

EMC & Security	FCC Class A, CE Mark, LVD
----------------	---------------------------



LCD170

ENVIRONMENT

Operating temperature	0°C ~ 40°C (32°F ~ 104°F)
Storage temperature	-20°C ~ 60°C (-4°F ~ 140°F)
Humidity	20% ~ 85% RH without condensation

DIMENSIONS

360 x 218 x 250 to 339 mm

WEIGHT

4,34 kg

VESA

VESA Mount 100 x 100



CUSTOMER
DISPLAY



MSR
READER



DALLAS
READER

